



Dry Guard

Frigid Fluid Company

Chemwatch: 5179-78
Version No: 3.1.1.1
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 29/05/2015
Print Date: 01/06/2015
Initial Date: Not Available
S.GHS.USA.EN

SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

Product Identifier

Product name	Dry Guard
Synonyms	Not Available
Proper shipping name	Formaldehyde solutions, flammable
Other means of identification	Not Available

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Use according to manufacturer's directions.
--------------------------	---

Details of the manufacturer/importer

Registered company name	Frigid Fluid Company
Address	11631 W Grand Ave Melrose Park 60164 IL United States
Telephone	+1 708-836-1215
Fax	Not Available
Website	Not Available
Email	Not Available

Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	1-800-424-9300
Other emergency telephone numbers	Not Available

SECTION 2 HAZARDS IDENTIFICATION

Classification of the substance or mixture

Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Classified as Dangerous Goods for transport purposes.



GHS Classification	Flammable Liquid Category 2, Metal Corrosion Category 1, Acute Toxicity (Oral) Category 3, Acute Toxicity (Dermal) Category 3, Acute Toxicity (Inhalation) Category 2, Skin Corrosion/Irritation Category 1B, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Carcinogen Category 1A, STOT - SE Category 1
--------------------	---

Label elements

GHS label elements	
--------------------	--

SIGNAL WORD	DANGER
-------------	--------

Hazard statement(s)

H225	Highly flammable liquid and vapour
H290	May be corrosive to metals
H301	Toxic if swallowed
H311	Toxic in contact with skin

Continued...

Dry Guard

H330	Fatal if inhaled
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H317	May cause an allergic skin reaction
H350	May cause cancer
H370	Causes damage to organs

Precautionary statement(s) Prevention

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

Precautionary statement(s) Response

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P307+P311	IF exposed: Call a POISON CENTER/doctor/physician/first aider

Precautionary statement(s) Storage

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

Precautionary statement(s) Disposal

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
50-00-0	21	<u>formaldehyde</u>
67-56-1	9-18	<u>methanol</u>
56-81-5	2-5	<u>glycerol</u>

SECTION 4 FIRST AID MEASURES

Description of first aid measures

Eye Contact	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> ▶ Immediately hold eyelids apart and flush the eye continuously with running water. ▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. ▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. ▶ Transport to hospital or doctor without delay. ▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.
Skin Contact	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> ▶ Immediately flush body and clothes with large amounts of water, using safety shower if available. ▶ Quickly remove all contaminated clothing, including footwear. ▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. ▶ Transport to hospital, or doctor.
Inhalation	<ul style="list-style-type: none"> ▶ If fumes or combustion products are inhaled remove from contaminated area. ▶ Lay patient down. Keep warm and rested. ▶ Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. ▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. ▶ Transport to hospital, or doctor, without delay. ▶ Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. ▶ Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). ▶ As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be

Dry Guard

	<ul style="list-style-type: none"> ▶ kept under medical observation even if no symptoms are (yet) manifested. ▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. <p>This must definitely be left to a doctor or person authorised by him/her. (ICSC13719)</p>
Ingestion	<ul style="list-style-type: none"> ▶ Avoid giving milk or oils. ▶ Avoid giving alcohol. ▶ IF SWALLOWED, REFER FOR MEDICAL ATTENTION, WHERE POSSIBLE, WITHOUT DELAY. ▶ For advice, contact a Poisons Information Centre or a doctor. ▶ Urgent hospital treatment is likely to be needed. ▶ In the mean time, qualified first-aid personnel should treat the patient following observation and employing supportive measures as indicated by the patient's condition. ▶ If the services of a medical officer or medical doctor are readily available, the patient should be placed in his/her care and a copy of the MSDS should be provided. Further action will be the responsibility of the medical specialist. ▶ If medical attention is not available on the worksite or surroundings send the patient to a hospital together with a copy of the MSDS. <p>Where medical attention is not immediately available or where the patient is more than 15 minutes from a hospital or unless instructed otherwise:</p> <ul style="list-style-type: none"> ▶ INDUCE vomiting with fingers down the back of the throat, ONLY IF CONSCIOUS. Lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. <p>NOTE: Wear a protective glove when inducing vomiting by mechanical means.</p> <ul style="list-style-type: none"> ▶ If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomitus.

Indication of any immediate medical attention and special treatment needed

Any material aspirated during vomiting may produce lung injury. Therefore emesis should not be induced mechanically or pharmacologically. Mechanical means should be used if it is considered necessary to evacuate the stomach contents; these include gastric lavage after endotracheal intubation. If spontaneous vomiting has occurred after ingestion, the patient should be monitored for difficult breathing, as adverse effects of aspiration into the lungs may be delayed up to 48 hours.

For acute or short-term repeated exposures to formaldehyde:

INGESTION:

- ▶ Patients present early with severe corrosion of the gastro-intestinal tract and systemic effects.
- ▶ Inflammation and ulceration may progress to strictures.
- ▶ Severe acidosis results from rapid conversion of formaldehyde to formic acid. Coma, hypotension, renal failure and apnoea complicate ingestion.
- ▶ Decontaminate by dilution with milk or water containing ammonium acetate; vomiting should be induced. Follow with gastric lavage using a weak ammonia solution (converts formaldehyde to relatively inert pentamethylenetetramine)
- ▶ Gastric lavage is warranted only in first 15 minutes following ingestion.

SKIN:

- ▶ Formaldehyde can combine with epidermal protein to produce a hapten-protein couple capable of sensitising T-lymphocytes. Subsequent exposures cause a type IV hypersensitivity reaction (i.e. allergic contact dermatitis). [Ellenhorn & Barceloux: Medical Toxicology]

For acute and short term repeated exposures to methanol:

- ▶ Toxicity results from accumulation of formaldehyde/formic acid.
- ▶ Clinical signs are usually limited to CNS, eyes and GI tract Severe metabolic acidosis may produce dyspnea and profound systemic effects which may become intractable. All symptomatic patients should have arterial pH measured. Evaluate airway, breathing and circulation.
- ▶ Stabilise obtunded patients by giving naloxone, glucose and thiamine.
- ▶ Decontaminate with Ipecac or lavage for patients presenting 2 hours post-ingestion. Charcoal does not absorb well; the usefulness of cathartic is not established.
- ▶ Forced diuresis is not effective; haemodialysis is recommended where peak methanol levels exceed 50 mg/dL (this correlates with serum bicarbonate levels below 18 mEq/L).
- ▶ Ethanol, maintained at levels between 100 and 150 mg/dL, inhibits formation of toxic metabolites and may be indicated when peak methanol levels exceed 20 mg/dL. An intravenous solution of ethanol in D5W is optimal.
- ▶ Folate, as leucovorin, may increase the oxidative removal of formic acid. 4-methylpyrazole may be an effective adjunct in the treatment. 8-Phenytoin may be preferable to diazepam for controlling seizure.

[Ellenhorn Barceloux: Medical Toxicology]

BIOLOGICAL EXPOSURE INDEX - BEI

Determinant	Index	Sampling Time	Comment
1. Methanol in urine	15 mg/l	End of shift	B, NS
2. Formic acid in urine	80 mg/gm creatinine	Before the shift at end of workweek	B, NS

B: Background levels occur in specimens collected from subjects **NOT** exposed.

NS: Non-specific determinant - observed following exposure to other materials.

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. Immediate administration of an appropriate spray, by a doctor or a person authorised by him/her should be considered.
(ICSC24419/24421)

SECTION 5 FIREFIGHTING MEASURES

Extinguishing media

	<ul style="list-style-type: none"> ▶ Water spray or fog. ▶ Foam. ▶ Dry chemical powder. ▶ BCF (where regulations permit). ▶ Carbon dioxide.
--	--

Special hazards arising from the substrate or mixture

Fire Incompatibility	▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result
-----------------------------	--

Advice for firefighters

Fire Fighting	▶ Alert Fire Brigade and tell them location and nature of hazard.
----------------------	---

	<ul style="list-style-type: none"> ▶ May be violently or explosively reactive. ▶ Wear breathing apparatus plus protective gloves in the event of a fire. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ If safe, switch off electrical equipment until vapour fire hazard removed. ▶ Use water delivered as a fine spray to control fire and cool adjacent area.
Fire/Explosion Hazard	<ul style="list-style-type: none"> ▶ Liquid and vapour are flammable. ▶ Moderate fire hazard when exposed to heat or flame. ▶ Vapour forms an explosive mixture with air. ▶ Moderate explosion hazard when exposed to heat or flame. ▶ Vapour may travel a considerable distance to source of ignition. ▶ Heating may cause expansion or decomposition leading to violent rupture of containers.

SECTION 6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Minor Spills	<ul style="list-style-type: none"> ▶ Remove all ignition sources. ▶ Clean up all spills immediately. ▶ Avoid breathing vapours and contact with skin and eyes. ▶ Control personal contact with the substance, by using protective equipment. ▶ Contain and absorb small quantities with vermiculite or other absorbent material. ▶ Wipe up.
Major Spills	<ul style="list-style-type: none"> ▶ Clear area of personnel and move upwind. ▶ Alert Fire Brigade and tell them location and nature of hazard. ▶ May be violently or explosively reactive. ▶ Wear full body protective clothing with breathing apparatus. ▶ Prevent, by any means available, spillage from entering drains or water course. ▶ No smoking, naked lights or ignition sources.

Personal Protective Equipment advice is contained in Section 8 of the MSDS.

SECTION 7 HANDLING AND STORAGE

Precautions for safe handling

Safe handling	<ul style="list-style-type: none"> ▶ Containers, even those that have been emptied, may contain explosive vapours. ▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers. ▶ DO NOT allow clothing wet with material to stay in contact with skin ▶ Avoid all personal contact, including inhalation. ▶ Wear protective clothing when risk of overexposure occurs. ▶ Use in a well-ventilated area. ▶ Prevent concentration in hollows and sumps.
Other information	<ul style="list-style-type: none"> ▶ Store in original containers in approved flammable liquid storage area. ▶ Store away from incompatible materials in a cool, dry, well-ventilated area. ▶ DO NOT store in pits, depressions, basements or areas where vapours may be trapped. ▶ No smoking, naked lights, heat or ignition sources. ▶ Storage areas should be clearly identified, well illuminated, clear of obstruction and accessible only to trained and authorised personnel - adequate security must be provided so that unauthorised personnel do not have access. ▶ Store according to applicable regulations for flammable materials for storage tanks, containers, piping, buildings, rooms, cabinets, allowable quantities and minimum storage distances.

Conditions for safe storage, including any incompatibilities

Suitable container	<ul style="list-style-type: none"> ▶ Packing as supplied by manufacturer. ▶ Plastic containers may only be used if approved for flammable liquid. ▶ Check that containers are clearly labelled and free from leaks. ▶ For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure. ▶ For materials with a viscosity of at least 2680 cSt.
Storage incompatibility	<ul style="list-style-type: none"> ▶ Avoid strong acids, bases. ▶ Avoid reaction with oxidising agents

PACKAGE MATERIAL INCOMPATIBILITIES

Not Available

SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

OCCUPATIONAL EXPOSURE LIMITS (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	formaldehyde	Formaldehyde	0.75 ppm	2 ppm	Not Available	see 1910.1048
US OSHA Permissible Exposure Levels (PELs) - Table Z2	formaldehyde	Formaldehyde	0.75 ppm	2 ppm	Not Available	see 1910.1048

Continued...


US ACGIH Threshold Limit Values (TLV)	formaldehyde	‡ Formaldehyde	Not Available	Not Available	0.3 ppm	TLV® Basis: URT & eye irr
US NIOSH Recommended Exposure Limits (RELs)	formaldehyde	Methanal, Methyl aldehyde, Methylene oxide / Formaldehyde solution [Note: Formalin is an aqueous solution that is 37% formaldehyde by weight; inhibited solutions usually contain 6-12% methyl alcohol. Also see specific listings for Formaldehyde and Methyl alcohol.]	0.016 ppm	Not Available	0.1 ppm	Ca See Appendix A
US OSHA Permissible Exposure Levels (PELs) - Table Z1	methanol	Methyl alcohol	260 mg/m3 / 200 ppm	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	methanol	Methanol	200 ppm	250 ppm	Not Available	TLV® Basis: Headache; eye dam; dizziness; nausea; BEI
US NIOSH Recommended Exposure Limits (RELs)	methanol	Carbinol, Columbian spirits, Methanol, Pyroligneous spirit, Wood alcohol, Wood naphtha, Wood spirit	260 mg/m3 / 200 ppm	325 mg/m3 / 250 ppm	Not Available	[skin]
US OSHA Permissible Exposure Levels (PELs) - Table Z1	glycerol	Glycerin / Glycerin - Respirable fraction	15 mg/m3 / 5 mg/m3	Not Available	Not Available	Total dust; (mist) / (mist)
US NIOSH Recommended Exposure Limits (RELs)	glycerol	Glycerin (anhydrous); Glycerol; Glycyl alcohol; 1,2,3-Propanetriol; Trihydroxypropane	Not Available	Not Available	Not Available	See Appendix D

EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
formaldehyde	Formaldehyde	Not Available	Not Available	Not Available
methanol	Methyl alcohol; (Methanol)	Not Available	Not Available	Not Available
glycerol	Glycerine (mist); (Glycerol; Glycerin)	30 mg/m3	310 mg/m3	2500 mg/m3

Ingredient	Original IDLH	Revised IDLH
formaldehyde	30 ppm	20 ppm
methanol	25,000 ppm	6,000 ppm
glycerol	Not Available	Not Available

Exposure controls

Appropriate engineering controls	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <ul style="list-style-type: none"> Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.
Personal protection	
Eye and face protection	<ul style="list-style-type: none"> Chemical goggles. Full face shield may be required for supplementary but never for primary protection of eyes. Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.
Skin protection	See Hand protection below
Hands/feet protection	<ul style="list-style-type: none"> Wear chemical protective gloves, e.g. PVC. Wear safety footwear or safety gumboots, e.g. Rubber When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots. <p>NOTE:</p> <ul style="list-style-type: none"> The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact. Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed. <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.</p>
Body protection	See Other protection below
Other protection	<ul style="list-style-type: none"> Overalls. PVC Apron. PVC protective suit may be required if exposure severe. Eyewash unit. Ensure there is ready access to a safety shower. <p>Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.</p>
Thermal hazards	Not Available

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-**

Respiratory protection

Type BAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the

Dry Guard

generated selection:

Dry Guard

Material	CPI
BUTYL	C
BUTYL/NEOPRENE	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
PE	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON	C
VITON/NEOPRENE	C

* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

"Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	BAX-AUS P2	-	BAX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	BAX-AUS / Class 1 P2	-
up to 100 x ES	-	BAX-2 P2	BAX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO₂), G = Agricultural chemicals, K = Ammonia(NH₃), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

Information on basic physical and chemical properties

Appearance	Clear flammable liquid with pungent odour; mixes with water.		
Physical state	Liquid	Relative density (Water = 1)	1.08
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Applicable	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	63	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	49	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	73	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	6	Volatile Component (%vol)	>85
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water (g/L)	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	~1	VOC g/L	Not Available

SECTION 10 STABILITY AND REACTIVITY

Reactivity	See section 7
Chemical stability	<ul style="list-style-type: none"> ▶ Presence of heat source and ignition source ▶ Unstable in the presence of incompatible materials. ▶ Product is considered stable. ▶ Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7

Continued...

Dry Guard

Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 TOXICOLOGICAL INFORMATION

Information on toxicological effects

Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects. There is strong evidence to suggest that this material can cause, if inhaled once, serious, irreversible damage of organs. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Inhalation of quantities of liquid mist may be extremely hazardous, even lethal due to spasm, extreme irritation of larynx and bronchi, chemical pneumonitis and pulmonary oedema.
Ingestion	The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion. Strong evidence exists that exposure to the material may produce serious irreversible damage (other than carcinogenesis, mutagenesis and teratogenesis) following a single exposure by swallowing. Swallowing of the liquid may cause aspiration into the lungs with the risk of chemical pneumonitis; serious consequences may result. (ICSC13733)
Skin Contact	The material can produce chemical burns following direct contact with the skin. There is strong evidence to suggest that this material, on a single contact with skin, can cause serious, irreversible damage of organs. Open cuts, abraded or irritated skin should not be exposed to this material. Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected. The material may cause severe inflammation of the skin either following direct contact or after a delay of some time. Repeated exposure can cause contact dermatitis which is characterised by redness, swelling and blistering.
Eye	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage. Irritation of the eyes may produce a heavy secretion of tears (lachrymation).
Chronic	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population. Long-term exposure to methanol vapour, at concentrations exceeding 3000 ppm, may produce cumulative effects characterised by gastrointestinal disturbances (nausea, vomiting), headache, ringing in the ears, insomnia, trembling, unsteady gait, vertigo, conjunctivitis and clouded or double vision. Liver and/or kidney injury may also result.

	TOXICITY	IRRITATION
Dry Guard	Not Available	Not Available
formaldehyde	Dermal (rabbit) LD50: 270 mg/kg ^[2]	Eye (human): 4 ppm/5m
	Inhalation (rat) LC50: 250 ppm/4h ^[2]	Eye (rabbit): 0.75 mg/24H SEVERE
	Oral (rat) LD50: 100 mg/kgm ^[2]	Skin (human): 0.15 mg/3d-I mild
		Skin (rabbit): 2 mg/24H SEVERE
methanol	Dermal (rabbit) LD50: 15800 mg/kg ^[2]	Eye (rabbit): 100 mg/24h-moderate
	Inhalation (rat) LC50: 64000 ppm/4h ^[2]	Eye (rabbit): 40 mg-moderate
	Oral (rat) LD50: >11872769 mg/kg ^[1]	Skin (rabbit): 20 mg/24 h-moderate
glycerol	dermal (guinea pig) LD50: 54000 mg/kg ^[1]	Not Available
	Oral (rat) LD50: >20<39800 mg/kg ^[1]	
Legend:	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's msds. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances	

FORMALDEHYDE	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact.
METHANOL	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
GLYCEROL	Asthma-like symptoms may continue for months or even years after exposure to the material ceases. This may be due to a non-allergenic condition known as reactive airways dysfunction syndrome (RADS) which can occur following exposure to high levels of highly irritating compound. Key criteria for the diagnosis of RADS include the absence of preceding respiratory disease, in a non-atopic individual, with abrupt onset of persistent asthma-like symptoms

within minutes to hours of a documented exposure to the irritant. A reversible airflow pattern, on spirometry, with the presence of moderate to severe bronchial hyperreactivity on methacholine challenge testing and the lack of minimal lymphocytic inflammation, without eosinophilia, have also been included in the criteria for diagnosis of RADS. RADS (or asthma) following an irritating inhalation is an infrequent disorder with rates related to the concentration of and duration of exposure to the irritating substance. Industrial bronchitis, on the other hand, is a disorder that occurs as result of exposure due to high concentrations of irritating substance (often particulate in nature) and is completely reversible after exposure ceases.

Acute Toxicity	✓	Carcinogenicity	✓
Skin Irritation/Corrosion	✓	Reproductivity	⊘
Serious Eye Damage/Irritation	✓	STOT - Single Exposure	✓
Respiratory or Skin sensitisation	✓	STOT - Repeated Exposure	⊘
Mutagenicity	⊘	Aspiration Hazard	⊘

Legend: ✓ – Data required to make classification available
 ✗ – Data available but does not fill the criteria for classification
 ⊘ – Data Not Available to make classification

CMR STATUS

CARCINOGEN	formaldehyde	US Environmental Defense Scorecard Recognized Carcinogens US Air Toxics Hot Spots TSD for Describing Available Cancer Potency Factors US NIOSH Recommended Exposure Limits (RELs) - Carcinogens	P65 2A Ca See Appendix A
EYE	formaldehyde	US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) - Eye	Toxic Air Contaminant: The Air Resources Board has identified this substance as a Toxic Air Contaminant. FORMALDEHYDE X
RESPIRATORY	formaldehyde	US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs) - Respiratory	X
SKIN	formaldehyde	US - Hawaii Air Contaminant Limits - Skin Designation US - Alaska Limits for Air Contaminants - Skin Designation US NIOSH Recommended Exposure Limits (RELs) - Skin US - Washington Permissible exposure limits of air contaminants - Skin US - Michigan Exposure Limits for Air Contaminants - Skin US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants - Skin US ACGIH Threshold Limit Values (TLV) - Skin US - California Permissible Exposure Limits for Chemical Contaminants - Skin US - North Carolina Permissible Exposure Limits (PELs) for Air Contaminants - Skin Designation [NLV] US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants - Skin US - Minnesota Permissible Exposure Limits (PELs) - Skin	X [skin] Yes S
	methanol	US - Hawaii Air Contaminant Limits - Skin Designation US - Alaska Limits for Air Contaminants - Skin Designation US NIOSH Recommended Exposure Limits (RELs) - Skin US - Washington Permissible exposure limits of air contaminants - Skin US - Michigan Exposure Limits for Air Contaminants - Skin US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants - Skin US ACGIH Threshold Limit Values (TLV) - Skin US - California Permissible Exposure Limits for Chemical Contaminants - Skin US - North Carolina Permissible Exposure Limits (PELs) for Air Contaminants - Skin Designation [NLV] US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants - Skin US - Minnesota Permissible Exposure Limits (PELs) - Skin	X [skin] Yes S

SECTION 12 ECOLOGICAL INFORMATION

Toxicity

DO NOT discharge into sewer or waterways.

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
formaldehyde	LOW (Half-life = 14 days)	LOW (Half-life = 2.97 days)
methanol	LOW	LOW
glycerol	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
formaldehyde	LOW (LogKOW = 0.35)
methanol	LOW (BCF = 10)
glycerol	LOW (LogKOW = -1.76)

Mobility in soil

Ingredient	Mobility
formaldehyde	HIGH (KOC = 1)
methanol	HIGH (KOC = 1)
glycerol	HIGH (KOC = 1)



SECTION 13 DISPOSAL CONSIDERATIONS

Waste treatment methods

Product / Packaging disposal	<ul style="list-style-type: none"> ▶ Containers may still present a chemical hazard/ danger when empty. ▶ Return to supplier for reuse/ recycling if possible. <p>Otherwise:</p> <ul style="list-style-type: none"> ▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill. ▶ Where possible retain label warnings and MSDS and observe all notices pertaining to the product. ▶ DO NOT allow wash water from cleaning or process equipment to enter drains. ▶ It may be necessary to collect all wash water for treatment before disposal.
-------------------------------------	--

SECTION 14 TRANSPORT INFORMATION

Labels Required

Labels Required	 
Marine Pollutant	NO

Land transport (DOT)

UN number	1198				
Packing group	III				
UN proper shipping name	Formaldehyde solutions, flammable				
Environmental hazard	No relevant data				
Transport hazard class(es)	<table border="0"> <tr> <td style="padding-right: 10px;">Class</td> <td style="border-left: 1px dashed black;">3</td> </tr> <tr> <td style="padding-right: 10px;">Subrisk</td> <td style="border-left: 1px dashed black;">8</td> </tr> </table>	Class	3	Subrisk	8
Class	3				
Subrisk	8				
Special precautions for user	Special provisions 176, B1, IB3, T4, TP1				

Air transport (ICAO-IATA / DGR)

UN number	1198														
Packing group	III														
UN proper shipping name	Formaldehyde solution, flammable														
Environmental hazard	No relevant data														
Transport hazard class(es)	<table border="0"> <tr> <td style="padding-right: 10px;">ICAO/IATA Class</td> <td style="border-left: 1px dashed black;">3</td> </tr> <tr> <td style="padding-right: 10px;">ICAO / IATA Subrisk</td> <td style="border-left: 1px dashed black;">8</td> </tr> <tr> <td style="padding-right: 10px;">ERG Code</td> <td style="border-left: 1px dashed black;">3Ci</td> </tr> </table>	ICAO/IATA Class	3	ICAO / IATA Subrisk	8	ERG Code	3Ci								
ICAO/IATA Class	3														
ICAO / IATA Subrisk	8														
ERG Code	3Ci														
Special precautions for user	<table border="0"> <tr> <td style="padding-right: 10px;">Special provisions</td> <td style="border-left: 1px dashed black;">A180</td> </tr> <tr> <td style="padding-right: 10px;">Cargo Only Packing Instructions</td> <td style="border-left: 1px dashed black;">365</td> </tr> <tr> <td style="padding-right: 10px;">Cargo Only Maximum Qty / Pack</td> <td style="border-left: 1px dashed black;">60 L</td> </tr> <tr> <td style="padding-right: 10px;">Passenger and Cargo Packing Instructions</td> <td style="border-left: 1px dashed black;">354</td> </tr> <tr> <td style="padding-right: 10px;">Passenger and Cargo Maximum Qty / Pack</td> <td style="border-left: 1px dashed black;">5 L</td> </tr> <tr> <td style="padding-right: 10px;">Passenger and Cargo Limited Quantity Packing Instructions</td> <td style="border-left: 1px dashed black;">Y342</td> </tr> <tr> <td style="padding-right: 10px;">Passenger and Cargo Limited Maximum Qty / Pack</td> <td style="border-left: 1px dashed black;">1 L</td> </tr> </table>	Special provisions	A180	Cargo Only Packing Instructions	365	Cargo Only Maximum Qty / Pack	60 L	Passenger and Cargo Packing Instructions	354	Passenger and Cargo Maximum Qty / Pack	5 L	Passenger and Cargo Limited Quantity Packing Instructions	Y342	Passenger and Cargo Limited Maximum Qty / Pack	1 L
Special provisions	A180														
Cargo Only Packing Instructions	365														
Cargo Only Maximum Qty / Pack	60 L														
Passenger and Cargo Packing Instructions	354														
Passenger and Cargo Maximum Qty / Pack	5 L														
Passenger and Cargo Limited Quantity Packing Instructions	Y342														
Passenger and Cargo Limited Maximum Qty / Pack	1 L														

Sea transport (IMDG-Code / GGVSee)

UN number	1198						
Packing group	III						
UN proper shipping name	FORMALDEHYDE SOLUTION, FLAMMABLE						
Environmental hazard	Not Applicable						
Transport hazard class(es)	<table border="0"> <tr> <td style="padding-right: 10px;">IMDG Class</td> <td style="border-left: 1px dashed black;">3</td> </tr> <tr> <td style="padding-right: 10px;">IMDG Subrisk</td> <td style="border-left: 1px dashed black;">8</td> </tr> </table>	IMDG Class	3	IMDG Subrisk	8		
IMDG Class	3						
IMDG Subrisk	8						
Special precautions for user	<table border="0"> <tr> <td style="padding-right: 10px;">EMS Number</td> <td style="border-left: 1px dashed black;">F-E , S-C</td> </tr> <tr> <td style="padding-right: 10px;">Special provisions</td> <td style="border-left: 1px dashed black;">Not Applicable</td> </tr> <tr> <td style="padding-right: 10px;">Limited Quantities</td> <td style="border-left: 1px dashed black;">5 L</td> </tr> </table>	EMS Number	F-E , S-C	Special provisions	Not Applicable	Limited Quantities	5 L
EMS Number	F-E , S-C						
Special provisions	Not Applicable						
Limited Quantities	5 L						

Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	formaldehyde	Y

IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	methanol	Y
---	----------	---

SECTION 15 REGULATORY INFORMATION

Safety, health and environmental regulations / legislation specific for the substance or mixture

formaldehyde(50-00-0) is found on the following regulatory lists	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - Idaho - Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US - California Proposition 65 - Reproductive Toxicity", "US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US EPA Carcinogens Listing", "US - Oregon Permissible Exposure Limits (Z-2)", "US - Oregon Permissible Exposure Limits (Z-1)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "US - Michigan Exposure Limits for Air Contaminants", "US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Mutagens", "US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - Alaska Limits for Air Contaminants", "US NIOSH Recommended Exposure Limits (RELs)", "US OSHA Carcinogens Listing", "US - Washington Permissible exposure limits of air contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift", "US OSHA Permissible Exposure Levels (PELs) - Table Z2", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity", "US - Minnesota Permissible Exposure Limits (PELs)", "US - California Proposition 65 - Carcinogens", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Idaho - Acceptable Maximum Peak Concentrations", "US ACGIH Threshold Limit Values (TLV)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens"
methanol(67-56-1) is found on the following regulatory lists	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - Idaho - Limits for Air Contaminants", "US - California Proposition 65 - Reproductive Toxicity", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Michigan Exposure Limits for Air Contaminants", "US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - Alaska Limits for Air Contaminants", "US NIOSH Recommended Exposure Limits (RELs)", "US - Washington Permissible exposure limits of air contaminants", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity", "US - Minnesota Permissible Exposure Limits (PELs)", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US OSHA Permissible Exposure Levels (PELs) - Table Z1"
glycerol(56-81-5) is found on the following regulatory lists	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - Idaho - Limits for Air Contaminants", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Michigan Exposure Limits for Air Contaminants", "US - Alaska Limits for Air Contaminants", "US NIOSH Recommended Exposure Limits (RELs)", "US - Washington Permissible exposure limits of air contaminants", "US - Minnesota Permissible Exposure Limits (PELs)", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US OSHA Permissible Exposure Levels (PELs) - Table Z1"

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y
China - IECS	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	Y
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
Legend:	Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

SECTION 16 OTHER INFORMATION

Other information

Ingredients with multiple cas numbers

Name	CAS No
formaldehyde	112068-71-0, 50-00-0, 8005-38-7, 8006-07-3, 8013-13-6
glycerol	29796-42-7, 30049-52-6, 37228-54-9, 56-81-5, 75398-78-6, 78630-16-7, 8013-25-0

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:
www.chemwatch.net

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other

Continued...

settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.