



## Perfect Tone

### Frigid Fluid Company

Chemwatch: 5184-00  
Version No: 3.1.1.1  
Safety Data Sheet according to OSHA HazCom Standard (2012) requirements

Chemwatch Hazard Alert Code: 3

Issue Date: 28/05/2015  
Print Date: 01/06/2015  
Initial Date: Not Available  
S.GHS.USA.EN

## SECTION 1 IDENTIFICATION OF THE SUBSTANCE / MIXTURE AND OF THE COMPANY / UNDERTAKING

### Product Identifier

Product name	Perfect Tone
Synonyms	Perfect Tone Arterial Fluid
Proper shipping name	Toxic liquids, corrosive, organic, n.o.s. (contains formaldehyde)
Other means of identification	Not Available

### Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Arterial embalming fluid.
--------------------------	---------------------------

### Details of the manufacturer/importer

Registered company name	Frigid Fluid Company
Address	11631 W Grand Ave Melrose Park 60164 IL United States
Telephone	+1 708-836-1215
Fax	Not Available
Website	Not Available
Email	Not Available

### Emergency telephone number

Association / Organisation	Not Available
Emergency telephone numbers	1-800-424-9300
Other emergency telephone numbers	Not Available

## SECTION 2 HAZARDS IDENTIFICATION

### Classification of the substance or mixture

Considered a Hazardous Substance by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200). Classified as Dangerous Goods for transport purposes.



GHS Classification	Flammable Liquid Category 4, Metal Corrosion Category 1, Acute Toxicity (Oral) Category 3, Acute Toxicity (Dermal) Category 3, Acute Toxicity (Inhalation) Category 2, Skin Corrosion/Irritation Category 1A, Serious Eye Damage Category 1, Skin Sensitizer Category 1, Carcinogen Category 1A, STOT - SE Category 2
--------------------	---

### Label elements

GHS label elements	
--------------------	--

SIGNAL WORD DANGER

### Hazard statement(s)

H227	Combustible liquid
H290	May be corrosive to metals
H301	Toxic if swallowed
H311	Toxic in contact with skin

Continued...

Perfect Tone

H330	Fatal if inhaled
H314	Causes severe skin burns and eye damage
H318	Causes serious eye damage
H317	May cause an allergic skin reaction
H350	May cause cancer
H371	May cause damage to organs

**Precautionary statement(s) Prevention**

P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260	Do not breathe dust/fume/gas/mist/vapours/spray.
P270	Do not eat, drink or smoke when using this product.
P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.

**Precautionary statement(s) Response**

P301+P310	IF SWALLOWED: Immediately call a POISON CENTER/doctor/physician/first aider
P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308+P313	IF exposed or concerned: Get medical advice/attention.

**Precautionary statement(s) Storage**

P403+P233	Store in a well-ventilated place. Keep container tightly closed.
P403+P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.

**Precautionary statement(s) Disposal**

P501	Dispose of contents/container to authorised chemical landfill or if organic to high temperature incineration
------	--

**SECTION 3 COMPOSITION / INFORMATION ON INGREDIENTS**

**Substances**

See section below for composition of Mixtures

**Mixtures**

CAS No	%[weight]	Name
50-00-0	14-18	<u>formaldehyde</u>
102-71-6	5-10	<u>triethanolamine</u>
67-56-1	4-6	<u>methanol</u>
64742-48-9.	4-6	<u>petroleum distillates HFP</u>

**SECTION 4 FIRST AID MEASURES**

**Description of first aid measures**

<b>Eye Contact</b>	<p>If this product comes in contact with the eyes:</p> <ul style="list-style-type: none"> <li>▶ Immediately hold eyelids apart and flush the eye continuously with running water.</li> <li>▶ Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>▶ Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes.</li> <li>▶ Transport to hospital or doctor without delay.</li> <li>▶ Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
<b>Skin Contact</b>	<p>If skin or hair contact occurs:</p> <ul style="list-style-type: none"> <li>▶ Immediately flush body and clothes with large amounts of water, using safety shower if available.</li> <li>▶ Quickly remove all contaminated clothing, including footwear.</li> <li>▶ Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre.</li> <li>▶ Transport to hospital, or doctor.</li> </ul>
<b>Inhalation</b>	<ul style="list-style-type: none"> <li>▶ If fumes or combustion products are inhaled remove from contaminated area.</li> <li>▶ Lay patient down. Keep warm and rested.</li> <li>▶ Prosthesis such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.</li> <li>▶ Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary.</li> <li>▶ Transport to hospital, or doctor, without delay.</li> <li>▶ Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema.</li> <li>▶ Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs).</li> </ul>

## Perfect Tone

	<ul style="list-style-type: none"> <li>▶ As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested.</li> <li>▶ Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered.</li> </ul> <p><b>This must definitely be left to a doctor or person authorised by him/her.</b> (ICSC13719)</p>
Ingestion	<ul style="list-style-type: none"> <li>▶ For advice, contact a Poisons Information Centre or a doctor at once.</li> <li>▶ Urgent hospital treatment is likely to be needed.</li> <li>▶ <b>If swallowed do NOT induce vomiting.</b></li> <li>▶ If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.</li> <li>▶ Observe the patient carefully.</li> <li>▶ Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.</li> <li>▶ Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.</li> <li>▶ Transport to hospital or doctor without delay.</li> </ul>

**Indication of any immediate medical attention and special treatment needed**

For acute or short-term repeated exposures to highly alkaline materials:

- ▶ Respiratory stress is uncommon but present occasionally because of soft tissue edema.
- ▶ Unless endotracheal intubation can be accomplished under direct vision, cricothyroidotomy or tracheotomy may be necessary.
- ▶ Oxygen is given as indicated.
- ▶ The presence of shock suggests perforation and mandates an intravenous line and fluid administration.
- ▶ Damage due to alkaline corrosives occurs by liquefaction necrosis whereby the saponification of fats and solubilisation of proteins allow deep penetration into the tissue.

Alkalis continue to cause damage after exposure.

INGESTION:

- ▶ Milk and water are the preferred diluents

No more than 2 glasses of water should be given to an adult.

- ▶ Neutralising agents should never be given since exothermic heat reaction may compound injury.

\* Catharsis and emesis are absolutely contra-indicated.

\* Activated charcoal does not absorb alkali.

\* Gastric lavage should not be used.

Supportive care involves the following:

- ▶ Withhold oral feedings initially.
- ▶ If endoscopy confirms transmucosal injury start steroids only within the first 48 hours.
- ▶ Carefully evaluate the amount of tissue necrosis before assessing the need for surgical intervention.
- ▶ Patients should be instructed to seek medical attention whenever they develop difficulty in swallowing (dysphagia).

SKIN AND EYE:

- ▶ Injury should be irrigated for 20-30 minutes.

Eye injuries require saline. [Ellenhorn & Barceloux: Medical Toxicology]

For acute or short-term repeated exposures to formaldehyde:

INGESTION:

- ▶ Patients present early with severe corrosion of the gastro-intestinal tract and systemic effects.
- ▶ Inflammation and ulceration may progress to strictures.
- ▶ Severe acidosis results from rapid conversion of formaldehyde to formic acid. Coma, hypotension, renal failure and apnoea complicate ingestion.
- ▶ Decontaminate by dilution with milk or water containing ammonium acetate; vomiting should be induced. Follow with gastric lavage using a weak ammonia solution (converts formaldehyde to relatively inert pentamethylenetetramine)
- ▶ Gastric lavage is warranted only in first 15 minutes following ingestion.

SKIN:

- ▶ Formaldehyde can combine with epidermal protein to produce a hapten-protein couple capable of sensitising T-lymphocytes. Subsequent exposures cause a type IV hypersensitivity reaction (i.e allergic contact dermatitis). [Ellenhorn & Barceloux: Medical Toxicology]

For acute and short term repeated exposures to methanol:

- ▶ Toxicity results from accumulation of formaldehyde/formic acid.
- ▶ Clinical signs are usually limited to CNS, eyes and GI tract Severe metabolic acidosis may produce dyspnea and profound systemic effects which may become intractable. All symptomatic patients should have arterial pH measured. Evaluate airway, breathing and circulation.
- ▶ Stabilise obtunded patients by giving naloxone, glucose and thiamine.
- ▶ Decontaminate with Ipecac or lavage for patients presenting 2 hours post-ingestion. Charcoal does not absorb well; the usefulness of cathartic is not established.
- ▶ Forced diuresis is not effective; haemodialysis is recommended where peak methanol levels exceed 50 mg/dL (this correlates with serum bicarbonate levels below 18 mEq/L).
- ▶ Ethanol, maintained at levels between 100 and 150 mg/dL, inhibits formation of toxic metabolites and may be indicated when peak methanol levels exceed 20 mg/dL. An intravenous solution of ethanol in D5W is optimal.
- ▶ Folate, as leucovorin, may increase the oxidative removal of formic acid. 4-methylpyrazole may be an effective adjunct in the treatment. 8-Phenytoin may be preferable to diazepam for controlling seizure.

[Ellenhorn Barceloux: Medical Toxicology]

## BIOLOGICAL EXPOSURE INDEX - BEI

Determinant	Index	Sampling Time	Comment
1. Methanol in urine	15 mg/l	End of shift	B, NS
2. Formic acid in urine	80 mg/gm creatinine	Before the shift at end of workweek	B, NS

B: Background levels occur in specimens collected from subjects **NOT** exposed.

NS: Non-specific determinant - observed following exposure to other materials.

Depending on the degree of exposure, periodic medical examination is indicated. The symptoms of lung oedema often do not manifest until a few hours have passed and they are aggravated by physical effort. Rest and medical observation is therefore essential. Immediate administration of an appropriate spray, by a doctor or a person authorised by him/her should be considered.  
(ICSC24419/24421)

**SECTION 5 FIREFIGHTING MEASURES****Extinguishing media**

	<ul style="list-style-type: none"> <li>▶ Water spray or fog.</li> <li>▶ Foam.</li> <li>▶ Dry chemical powder.</li> <li>▶ BCF (where regulations permit).</li> <li>▶ Carbon dioxide.</li> </ul>
--	--

Continued...

**Special hazards arising from the substrate or mixture**

<b>Fire Incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result</li> </ul>
-----------------------------	--

**Advice for firefighters**

<b>Fire Fighting</b>	<ul style="list-style-type: none"> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Use fire fighting procedures suitable for surrounding area.</li> <li>▶ <b>Do not approach containers suspected to be hot.</b></li> <li>▶ Cool fire exposed containers with water spray from a protected location.</li> </ul>
<b>Fire/Explosion Hazard</b>	<ul style="list-style-type: none"> <li>▶ Combustible.</li> <li>▶ Slight fire hazard when exposed to heat or flame.</li> <li>▶ Heating may cause expansion or decomposition leading to violent rupture of containers.</li> <li>▶ On combustion, may emit toxic fumes of carbon monoxide (CO).</li> <li>▶ May emit acrid smoke.</li> <li>▶ Mists containing combustible materials may be explosive.</li> </ul>

**SECTION 6 ACCIDENTAL RELEASE MEASURES****Personal precautions, protective equipment and emergency procedures**

<b>Minor Spills</b>	<ul style="list-style-type: none"> <li>▶ Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of material.</li> <li>▶ Check regularly for spills and leaks.</li> <li>▶ Remove all ignition sources.</li> <li>▶ Clean up all spills immediately.</li> <li>▶ Avoid breathing vapours and contact with skin and eyes.</li> <li>▶ Control personal contact with the substance, by using protective equipment.</li> </ul>
<b>Major Spills</b>	<ul style="list-style-type: none"> <li>▶ Clear area of personnel and move upwind.</li> <li>▶ Alert Fire Brigade and tell them location and nature of hazard.</li> <li>▶ Wear full body protective clothing with breathing apparatus.</li> <li>▶ Prevent, by any means available, spillage from entering drains or water course.</li> <li>▶ Consider evacuation (or protect in place).</li> <li>▶ Stop leak if safe to do so.</li> </ul>
	Personal Protective Equipment advice is contained in Section 8 of the MSDS.

**SECTION 7 HANDLING AND STORAGE****Precautions for safe handling**

<b>Safe handling</b>	<p>The conductivity of this material may make it a static accumulator. A liquid is typically considered nonconductive if its conductivity is below 100 pS/m and is considered semi-conductive if its conductivity is below 10 000 pS/m. Whether a liquid is nonconductive or semi-conductive, the precautions are the same. A number of factors, for example liquid temperature, presence of contaminants, and anti-static additives can greatly influence the conductivity of a liquid.</p> <ul style="list-style-type: none"> <li>▶ Containers, even those that have been emptied, may contain explosive vapours.</li> <li>▶ Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>▶ <b>DO NOT allow clothing wet with material to stay in contact with skin</b></li> <li>▶ Electrostatic discharge may be generated during pumping - this may result in fire.</li> <li>▶ Ensure electrical continuity by bonding and grounding (earthing) all equipment.</li> <li>▶ Restrict line velocity during pumping in order to avoid generation of electrostatic discharge (<math>\leq 1</math> m/sec until fill pipe submerged to twice its diameter, then <math>\leq 7</math> m/sec).</li> </ul>
<b>Other information</b>	<ul style="list-style-type: none"> <li>▶ <b>DO NOT store near acids, or oxidising agents</b></li> <li>▶ Store in original containers.</li> <li>▶ Keep containers securely sealed.</li> <li>▶ Store in a cool, dry, well-ventilated area.</li> <li>▶ Store away from incompatible materials and foodstuff containers.</li> <li>▶ Protect containers against physical damage and check regularly for leaks.</li> <li>▶ Observe manufacturer's storage and handling recommendations contained within this MSDS.</li> </ul>

**Conditions for safe storage, including any incompatibilities**

<b>Suitable container</b>	<ul style="list-style-type: none"> <li>▶ Lined metal can, lined metal pail/ can.</li> <li>▶ Plastic pail.</li> <li>▶ Polyliner drum.</li> <li>▶ Packing as recommended by manufacturer.</li> <li>▶ Check all containers are clearly labelled and free from leaks.</li> </ul> <p>For low viscosity materials</p> <ul style="list-style-type: none"> <li>▶ Drums and jerricans must be of the non-removable head type.</li> </ul>
<b>Storage incompatibility</b>	<ul style="list-style-type: none"> <li>▶ Avoid strong acids, bases.</li> <li>▶ Avoid reaction with oxidising agents</li> </ul>

**PACKAGE MATERIAL INCOMPATIBILITIES**

Not Available

**SECTION 8 EXPOSURE CONTROLS / PERSONAL PROTECTION****Control parameters****OCCUPATIONAL EXPOSURE LIMITS (OEL)****INGREDIENT DATA**

Continued...

## Perfect Tone

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US OSHA Permissible Exposure Levels (PELs) - Table Z1	formaldehyde	Formaldehyde	0.75 ppm	2 ppm	Not Available	see 1910.1048
US OSHA Permissible Exposure Levels (PELs) - Table Z2	formaldehyde	Formaldehyde	0.75 ppm	2 ppm	Not Available	see 1910.1048
US ACGIH Threshold Limit Values (TLV)	formaldehyde	‡ Formaldehyde	Not Available	Not Available	0.3 ppm	TLV® Basis: URT & eye irr
US NIOSH Recommended Exposure Limits (RELs)	formaldehyde	Methanal, Methyl aldehyde, Methylene oxide / Formaldehyde solution [Note: Formalin is an aqueous solution that is 37% formaldehyde by weight; inhibited solutions usually contain 6-12% methyl alcohol. Also see specific listings for Formaldehyde and Methyl alcohol.]	0.016 ppm	Not Available	0.1 ppm	Ca See Appendix A
US ACGIH Threshold Limit Values (TLV)	triethanolamine	Triethanolamine	5 mg/m3	Not Available	Not Available	TLV® Basis: Eye & skin irr; BEIA
US OSHA Permissible Exposure Levels (PELs) - Table Z1	methanol	Methyl alcohol	260 mg/m3 / 200 ppm	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	methanol	Methanol	200 ppm	250 ppm	Not Available	TLV® Basis: Headache; eye dam; dizziness; nausea; BEI
US NIOSH Recommended Exposure Limits (RELs)	methanol	Carbinol, Columbian spirits, Methanol, Pyroligneous spirit, Wood alcohol, Wood naphtha, Wood spirit	260 mg/m3 / 200 ppm	325 mg/m3 / 250 ppm	Not Available	[skin]

## EMERGENCY LIMITS

Ingredient	Material name	TEEL-1	TEEL-2	TEEL-3
formaldehyde	Formaldehyde	Not Available	Not Available	Not Available
triethanolamine	Triethanolamine; (Trihydroxytriethylamine)	15 mg/m3	51 mg/m3	1100 mg/m3
methanol	Methyl alcohol; (Methanol)	Not Available	Not Available	Not Available
petroleum distillates HFP	Naphtha, hydrotreated heavy; (Isopar L-rev 2)	171 ppm	171 ppm	570 ppm
petroleum distillates HFP	Solvent naphtha, petroleum, medium aliphatic; (Mineral spirits, naphtha)	0.32 mg/m3	3.5 mg/m3	21 mg/m3

Ingredient	Original IDLH	Revised IDLH
formaldehyde	30 ppm	20 ppm
triethanolamine	Not Available	Not Available
methanol	25,000 ppm	6,000 ppm
petroleum distillates HFP	Not Available	Not Available

## Exposure controls

<b>Appropriate engineering controls</b>	<p>Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection.</p> <p>The basic types of engineering controls are:</p> <p>Process controls which involve changing the way a job activity or process is done to reduce the risk.</p> <p>Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.</p>
<b>Personal protection</b>	
<b>Eye and face protection</b>	<ul style="list-style-type: none"> <li>▶ Chemical goggles.</li> <li>▶ Full face shield may be required for supplementary but never for primary protection of eyes.</li> <li>▶ Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task. This should include a review of lens absorption and adsorption for the class of chemicals in use and an account of injury experience. Medical and first-aid personnel should be trained in their removal and suitable equipment should be readily available.</li> </ul>
<b>Skin protection</b>	See Hand protection below
<b>Hands/feet protection</b>	<ul style="list-style-type: none"> <li>▶ Wear chemical protective gloves, e.g. PVC.</li> <li>▶ Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.</li> </ul> <p><b>NOTE:</b></p> <ul style="list-style-type: none"> <li>▶ The material may produce skin sensitisation in predisposed individuals. Care must be taken, when removing gloves and other protective equipment, to avoid all possible skin contact.</li> <li>▶ Contaminated leather items, such as shoes, belts and watch-bands should be removed and destroyed.</li> </ul> <p>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer.</p>
<b>Body protection</b>	See Other protection below
<b>Other protection</b>	<ul style="list-style-type: none"> <li>▶ Overalls.</li> <li>▶ PVC Apron.</li> <li>▶ PVC protective suit may be required if exposure severe.</li> <li>▶ Eyewash unit.</li> </ul>

	▶ Ensure there is ready access to a safety shower.
<b>Thermal hazards</b>	Not Available

### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the **computer-generated** selection:

Perfect Tone

Material	CPI
BUTYL	C
BUTYL/NEOPRENE	C
NAT+NEOPR+NITRILE	C
NATURAL RUBBER	C
NATURAL+NEOPRENE	C
NEOPRENE	C
NEOPRENE/NATURAL	C
NITRILE	C
PE	C
PE/EVAL/PE	C
PVA	C
PVC	C
PVDC/PE/PVDC	C
SARANEX-23	C
SARANEX-23 2-PLY	C
TEFLON	C
VITON	C
VITON/NEOPRENE	C

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

### Respiratory protection

Type BKAX-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	BKAX-AUS P2	-	BKAX-PAPR-AUS / Class 1 P2
up to 50 x ES	-	BKAX-AUS / Class 1 P2	-
up to 100 x ES	-	BKAX-2 P2	BKAX-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO<sub>2</sub>), G = Agricultural chemicals, K = Ammonia(NH<sub>3</sub>), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

## SECTION 9 PHYSICAL AND CHEMICAL PROPERTIES

### Information on basic physical and chemical properties

<b>Appearance</b>	Pink, opaque, translucent liquid with pungent odour; mixes with water.		
<b>Physical state</b>	Liquid	<b>Relative density (Water = 1)</b>	1.05
<b>Odour</b>	Not Available	<b>Partition coefficient n-octanol / water</b>	Not Available
<b>Odour threshold</b>	Not Available	<b>Auto-ignition temperature (°C)</b>	Not Available
<b>pH (as supplied)</b>	Not Available	<b>Decomposition temperature</b>	Not Available
<b>Melting point / freezing point (°C)</b>	Not Available	<b>Viscosity (cSt)</b>	Not Available
<b>Initial boiling point and boiling range (°C)</b>	64	<b>Molecular weight (g/mol)</b>	Not Applicable
<b>Flash point (°C)</b>	82 (TCC)	<b>Taste</b>	Not Available
<b>Evaporation rate</b>	Not Available	<b>Explosive properties</b>	Not Available
<b>Flammability</b>	Combustible.	<b>Oxidising properties</b>	Not Available
<b>Upper Explosive Limit (%)</b>	73	<b>Surface Tension (dyn/cm or mN/m)</b>	Not Available
<b>Lower Explosive Limit (%)</b>	6	<b>Volatile Component (%vol)</b>	>50
<b>Vapour pressure (kPa)</b>	Not Available	<b>Gas group</b>	Not Available
<b>Solubility in water (g/L)</b>	Miscible	<b>pH as a solution (1%)</b>	Not Available
<b>Vapour density (Air = 1)</b>	>1	<b>VOC g/L</b>	Not Available

## SECTION 10 STABILITY AND REACTIVITY

<b>Reactivity</b>	See section 7
<b>Chemical stability</b>	<ul style="list-style-type: none"> <li>▶ Unstable in the presence of incompatible materials.</li> <li>▶ Product is considered stable.</li> <li>▶ Hazardous polymerisation will not occur.</li> </ul>
<b>Possibility of hazardous reactions</b>	See section 7
<b>Conditions to avoid</b>	See section 7
<b>Incompatible materials</b>	See section 7
<b>Hazardous decomposition products</b>	See section 5

## SECTION 11 TOXICOLOGICAL INFORMATION

## Information on toxicological effects

<b>Inhaled</b>	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may produce toxic effects. Inhalation of vapours may cause drowsiness and dizziness. This may be accompanied by sleepiness, reduced alertness, loss of reflexes, lack of co-ordination, and vertigo. Limited evidence exists that this substance may cause irreversible mutations (though not lethal) even following a single exposure.
<b>Ingestion</b>	<b>Toxic effects</b> may result from the accidental ingestion of the material; animal experiments indicate that ingestion of less than 40 gram may be fatal or may produce serious damage to the health of the individual. The material can produce chemical burns within the oral cavity and gastrointestinal tract following ingestion.
<b>Skin Contact</b>	Skin contact with the material may produce toxic effects; systemic effects may result following absorption. The material can produce chemical burns following direct contact with the skin. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.
<b>Eye</b>	The material can produce chemical burns to the eye following direct contact. Vapours or mists may be extremely irritating. If applied to the eyes, this material causes severe eye damage.
<b>Chronic</b>	Studies show that inhaling this substance for over a long period (e.g. in an occupational setting) may increase the risk of cancer. Skin contact with the material is more likely to cause a sensitisation reaction in some persons compared to the general population. Substance accumulation, in the human body, may occur and may cause some concern following repeated or long-term occupational exposure. There is some evidence that inhaling this product is more likely to cause a sensitisation reaction in some persons compared to the general population. There has been some concern that this material can cause cancer or mutations but there is not enough data to make an assessment.

Perfect Tone	TOXICITY	IRRITATION
	Not Available	Not Available
formaldehyde	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 270 mg/kg <sup>[2]</sup>	Eye (human): 4 ppm/5m
	Inhalation (rat) LC50: 250 ppm/4h <sup>[2]</sup>	Eye (rabbit): 0.75 mg/24H SEVERE
	Oral (rat) LD50: 100 mg/kgm <sup>[2]</sup>	Skin (human): 0.15 mg/3d-I mild Skin (rabbit): 2 mg/24H SEVERE
triethanolamine	TOXICITY	IRRITATION
	dermal (rat) LD50: >18080 mg/kg <sup>[2]</sup>	Eye (rabbit): 0.1 ml -
	Oral (rat) LD50: 5559.6 mg/kg(female) <sup>1[2]</sup>	Eye (rabbit): 10 mg - mild Eye (rabbit): 5.62 mg - SEVERE minor conjunctival irritation minor iritis, no corneal injury * no irritation * Skin (human): 15 mg/3d (int)-mild Skin (rabbit): 4 h occluded Skin (rabbit): 560 mg/24 hr- mild with significant discharge;
methanol	TOXICITY	IRRITATION
	Dermal (rabbit) LD50: 15800 mg/kg <sup>[2]</sup>	Eye (rabbit): 100 mg/24h-moderate
	Inhalation (rat) LC50: 64000 ppm/4h <sup>[2]</sup>	Eye (rabbit): 40 mg-moderate Skin (rabbit): 20 mg/24 h-moderate
petroleum distillates HFP	TOXICITY	IRRITATION
	dermal (rat) LD50: >28000 mg/kg*n <sup>[2]</sup>	* [Shell - Canada]

	Oral (rat) LD50: >19650 mg/kgd <sup>[2]</sup>
<b>Legend:</b>	1. Value obtained from Europe ECHA Registered Substances - Acute toxicity 2. * Value obtained from manufacturer's msds. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances
<b>TRIETHANOLAMINE</b>	Lachrymation, diarrhoea, convulsions, urinary tract changes, changes in bladder weight, changes in testicular weight, changes in thymus weight, changes in liver weight, dermatitis after systemic exposure, kidney, ureter, bladder tumours recorded. Equivocal tumourigen by RTECS criteria. Dermal rabbit value quoted above is for occluded patch in male or female animals * Union Carbide
<b>METHANOL</b>	The material may cause skin irritation after prolonged or repeated exposure and may produce on contact skin redness, swelling, the production of vesicles, scaling and thickening of the skin.
<b>PETROLEUM DISTILLATES HFP</b>	<b>for petroleum:</b> This product contains benzene which is known to cause acute myeloid leukaemia and n-hexane which has been shown to metabolize to compounds which are neuropathic. This product contains toluene. There are indications from animal studies that prolonged exposure to high concentrations of toluene may lead to hearing loss. This product contains ethyl benzene and naphthalene from which there is evidence of tumours in rodents <b>Carcinogenicity:</b> Inhalation exposure to mice causes liver tumours, which are not considered relevant to humans. Inhalation exposure to rats causes kidney tumours which are not considered relevant to humans. <b>Mutagenicity:</b> There is a large database of mutagenicity studies on gasoline and gasoline blending streams, which use a wide variety of endpoints and give predominantly negative results. data for CAS 64742-88-7 i.e. CCINFO record 1441735
<b>FORMALDEHYDE &amp; TRIETHANOLAMINE</b>	The following information refers to contact allergens as a group and may not be specific to this product. Contact allergies quickly manifest themselves as contact eczema, more rarely as urticaria or Quincke's oedema. The pathogenesis of contact eczema involves a cell-mediated (T lymphocytes) immune reaction of the delayed type. Other allergic skin reactions, e.g. contact urticaria, involve antibody-mediated immune reactions. The significance of the contact allergen is not simply determined by its sensitisation potential: the distribution of the substance and the opportunities for contact with it are equally important. A weakly sensitising substance which is widely distributed can be a more important allergen than one with stronger sensitising potential with which few individuals come into contact.

<b>Acute Toxicity</b>	✓	<b>Carcinogenicity</b>	✓
<b>Skin Irritation/Corrosion</b>	✓	<b>Reproductivity</b>	⊘
<b>Serious Eye Damage/Irritation</b>	✓	<b>STOT - Single Exposure</b>	✓
<b>Respiratory or Skin sensitisation</b>	✓	<b>STOT - Repeated Exposure</b>	⊘
<b>Mutagenicity</b>	⊘	<b>Aspiration Hazard</b>	⊘

**Legend:** ✓ - Data required to make classification available  
 ✗ - Data available but does not fill the criteria for classification  
 ⊘ - Data Not Available to make classification

**CMR STATUS**

<b>CARCINOGEN</b>	formaldehyde	US Environmental Defense Scorecard Recognized Carcinogens US Air Toxics Hot Spots TSD for Describing Available Cancer Potency Factors US NIOSH Recommended Exposure Limits (RELs) - Carcinogens	P65 2A Ca See Appendix A
<b>EYE</b>	formaldehyde	US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs) - Eye	Toxic Air Contaminant: The Air Resources Board has identified this substance as a Toxic Air Contaminant. FORMALDEHYDE X
<b>RESPIRATORY</b>	formaldehyde	US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs) - Respiratory	X
<b>SKIN</b>	formaldehyde	US - Hawaii Air Contaminant Limits - Skin Designation US - Alaska Limits for Air Contaminants - Skin Designation US NIOSH Recommended Exposure Limits (RELs) - Skin US - Washington Permissible exposure limits of air contaminants - Skin US - Michigan Exposure Limits for Air Contaminants - Skin US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants - Skin US ACGIH Threshold Limit Values (TLV) - Skin US - California Permissible Exposure Limits for Chemical Contaminants - Skin US - North Carolina Permissible Exposure Limits (PELs) for Air Contaminants - Skin Designation [NLV] US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants - Skin US - Minnesota Permissible Exposure Limits (PELs) - Skin	X [skin] Yes S
	methanol	US - Hawaii Air Contaminant Limits - Skin Designation US - Alaska Limits for Air Contaminants - Skin Designation US NIOSH Recommended Exposure Limits (RELs) - Skin US - Washington Permissible exposure limits of air contaminants - Skin US - Michigan Exposure Limits for Air Contaminants - Skin US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants - Skin US ACGIH Threshold Limit Values (TLV) - Skin US - California Permissible Exposure Limits for Chemical Contaminants - Skin US - North Carolina Permissible Exposure Limits (PELs) for Air Contaminants - Skin Designation [NLV] US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants - Skin US - Minnesota Permissible Exposure Limits (PELs) - Skin	X [skin] Yes S

**SECTION 12 ECOLOGICAL INFORMATION**

**Toxicity**

DO NOT discharge into sewer or waterways.

**Persistence and degradability**

## Perfect Tone

Ingredient	Persistence: Water/Soil	Persistence: Air
formaldehyde	LOW (Half-life = 14 days)	LOW (Half-life = 2.97 days)
triethanolamine	LOW	LOW
methanol	LOW	LOW

## Bioaccumulative potential

Ingredient	Bioaccumulation
formaldehyde	LOW (LogKOW = 0.35)
triethanolamine	LOW (BCF = 4)
methanol	LOW (BCF = 10)

## Mobility in soil

Ingredient	Mobility
formaldehyde	HIGH (KOC = 1)
triethanolamine	LOW (KOC = 10)
methanol	HIGH (KOC = 1)

## SECTION 13 DISPOSAL CONSIDERATIONS

## Waste treatment methods

<b>Product / Packaging disposal</b>	<ul style="list-style-type: none"> <li>▶ Containers may still present a chemical hazard/ danger when empty.</li> <li>▶ Return to supplier for reuse/ recycling if possible.</li> </ul> <p>Otherwise:</p> <ul style="list-style-type: none"> <li>▶ If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.</li> <li>▶ Where possible retain label warnings and MSDS and observe all notices pertaining to the product.</li> <li>▶ <b>DO NOT allow wash water from cleaning or process equipment to enter drains.</b></li> <li>▶ It may be necessary to collect all wash water for treatment before disposal.</li> </ul>
-------------------------------------	--

## SECTION 14 TRANSPORT INFORMATION

## Labels Required

<b>Labels Required</b>	
<b>Marine Pollutant</b>	NO

## Land transport (DOT)

<b>UN number</b>	2927				
<b>Packing group</b>	II				
<b>UN proper shipping name</b>	Toxic liquids, corrosive, organic, n.o.s. (contains formaldehyde)				
<b>Environmental hazard</b>	No relevant data				
<b>Transport hazard class(es)</b>	<table border="0"> <tr> <td style="padding-right: 5px;">Class</td> <td style="border-left: 1px dashed black; padding-left: 5px;">6.1</td> </tr> <tr> <td style="padding-right: 5px;">Subrisk</td> <td style="border-left: 1px dashed black; padding-left: 5px;">8</td> </tr> </table>	Class	6.1	Subrisk	8
Class	6.1				
Subrisk	8				
<b>Special precautions for user</b>	Special provisions   IB2, T11, TP2, TP27				

## Air transport (ICAO-IATA / DGR)

<b>UN number</b>	2927										
<b>Packing group</b>	II										
<b>UN proper shipping name</b>	Toxic liquid, corrosive, organic, n.o.s. * (contains formaldehyde)										
<b>Environmental hazard</b>	No relevant data										
<b>Transport hazard class(es)</b>	<table border="0"> <tr> <td style="padding-right: 5px;">ICAO/IATA Class</td> <td style="border-left: 1px dashed black; padding-left: 5px;">6.1</td> </tr> <tr> <td style="padding-right: 5px;">ICAO / IATA Subrisk</td> <td style="border-left: 1px dashed black; padding-left: 5px;">8</td> </tr> <tr> <td style="padding-right: 5px;">ERG Code</td> <td style="border-left: 1px dashed black; padding-left: 5px;">6C</td> </tr> </table>	ICAO/IATA Class	6.1	ICAO / IATA Subrisk	8	ERG Code	6C				
ICAO/IATA Class	6.1										
ICAO / IATA Subrisk	8										
ERG Code	6C										
<b>Special precautions for user</b>	<table border="0"> <tr> <td style="padding-right: 5px;">Special provisions</td> <td style="border-left: 1px dashed black; padding-left: 5px;">A4A137</td> </tr> <tr> <td style="padding-right: 5px;">Cargo Only Packing Instructions</td> <td style="border-left: 1px dashed black; padding-left: 5px;">660</td> </tr> <tr> <td style="padding-right: 5px;">Cargo Only Maximum Qty / Pack</td> <td style="border-left: 1px dashed black; padding-left: 5px;">30 L</td> </tr> <tr> <td style="padding-right: 5px;">Passenger and Cargo Packing Instructions</td> <td style="border-left: 1px dashed black; padding-left: 5px;">653</td> </tr> <tr> <td style="padding-right: 5px;">Passenger and Cargo Maximum Qty / Pack</td> <td style="border-left: 1px dashed black; padding-left: 5px;">1 L</td> </tr> </table>	Special provisions	A4A137	Cargo Only Packing Instructions	660	Cargo Only Maximum Qty / Pack	30 L	Passenger and Cargo Packing Instructions	653	Passenger and Cargo Maximum Qty / Pack	1 L
Special provisions	A4A137										
Cargo Only Packing Instructions	660										
Cargo Only Maximum Qty / Pack	30 L										
Passenger and Cargo Packing Instructions	653										
Passenger and Cargo Maximum Qty / Pack	1 L										

Passenger and Cargo Limited Quantity Packing Instructions	Y640
Passenger and Cargo Limited Maximum Qty / Pack	0.5 L

**Sea transport (IMDG-Code / GGVSee)**

<b>UN number</b>	2927
<b>Packing group</b>	II
<b>UN proper shipping name</b>	TOXIC LIQUID, CORROSIVE, ORGANIC, N.O.S. (contains formaldehyde)
<b>Environmental hazard</b>	Not Applicable
<b>Transport hazard class(es)</b>	IMDG Class : 6.1 IMDG Subrisk : 8
<b>Special precautions for user</b>	EMS Number : F-A , S-B Special provisions : 274 Limited Quantities : 100 mL

**Transport in bulk according to Annex II of MARPOL 73 / 78 and the IBC code**

Source	Ingredient	Pollution Category
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	formaldehyde	Y
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	triethanolamine	Z
IMO MARPOL 73/78 (Annex II) - List of Noxious Liquid Substances Carried in Bulk	methanol	Y

**SECTION 15 REGULATORY INFORMATION****Safety, health and environmental regulations / legislation specific for the substance or mixture**

<b>formaldehyde(50-00-0) is found on the following regulatory lists</b>	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - Idaho - Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV) - Carcinogens", "US - California Proposition 65 - Reproductive Toxicity", "US National Toxicology Program (NTP) 13th Report Part A Known to be Human Carcinogens", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US EPA Carcinogens Listing", "US - Oregon Permissible Exposure Limits (Z-2)", "US - Oregon Permissible Exposure Limits (Z-1)", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "US - Michigan Exposure Limits for Air Contaminants", "US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Mutagens", "US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - Alaska Limits for Air Contaminants", "US NIOSH Recommended Exposure Limits (RELs)", "US OSHA Carcinogens Listing", "US - Washington Permissible exposure limits of air contaminants", "US - Wyoming Toxic and Hazardous Substances Table Z-2 Acceptable ceiling concentration, Acceptable maximum peak above the acceptable ceiling concentration for an 8-hr shift", "US OSHA Permissible Exposure Levels (PELs) - Table Z2", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity", "US - Minnesota Permissible Exposure Limits (PELs)", "US - California Proposition 65 - Carcinogens", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US - Idaho - Acceptable Maximum Peak Concentrations", "US ACGIH Threshold Limit Values (TLV)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US OSHA Permissible Exposure Levels (PELs) - Table Z1", "US - New Jersey Right to Know - Special Health Hazard Substance List (SHHSL): Carcinogens"
<b>triethanolamine(102-71-6) is found on the following regulatory lists</b>	"US - California Permissible Exposure Limits for Chemical Contaminants", "International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs", "US ACGIH Threshold Limit Values (TLV)", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"
<b>methanol(67-56-1) is found on the following regulatory lists</b>	"US - Tennessee Occupational Exposure Limits - Limits For Air Contaminants", "US - Hawaii Air Contaminant Limits", "US - California Permissible Exposure Limits for Chemical Contaminants", "US - California Proposition 65 - No Significant Risk Levels (NSRLs) for Carcinogens", "US - Idaho - Limits for Air Contaminants", "US - California Proposition 65 - Reproductive Toxicity", "US - Vermont Permissible Exposure Limits Table Z-1-A Final Rule Limits for Air Contaminants", "US - Oregon Permissible Exposure Limits (Z-1)", "US - Michigan Exposure Limits for Air Contaminants", "US - California - Proposition 65 - Priority List for the Development of MADLs for Chemicals Causing Reproductive Toxicity", "US - California OEHHA/ARB - Acute Reference Exposure Levels and Target Organs (RELs)", "US - Washington Toxic air pollutants and their ASIL, SQER and de minimis emission values", "US - Alaska Limits for Air Contaminants", "US NIOSH Recommended Exposure Limits (RELs)", "US - Washington Permissible exposure limits of air contaminants", "US Spacecraft Maximum Allowable Concentrations (SMACs) for Airborne Contaminants", "US Priority List for the Development of Proposition 65 Safe Harbor Levels - No Significant Risk Levels (NSRLs) for Carcinogens and Maximum Allowable Dose Levels (MADLs) for Chemicals Causing Reproductive Toxicity", "US - Minnesota Permissible Exposure Limits (PELs)", "US - Vermont Permissible Exposure Limits Table Z-1-A Transitional Limits for Air Contaminants", "US ACGIH Threshold Limit Values (TLV)", "US - California OEHHA/ARB - Chronic Reference Exposure Levels and Target Organs (CRELs)", "US - Wyoming Toxic and Hazardous Substances Table Z1 Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory", "US OSHA Permissible Exposure Levels (PELs) - Table Z1"
<b>petroleum distillates HFP(64742-48-9.) is found on the following regulatory lists</b>	"US - Michigan Exposure Limits for Air Contaminants", "US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory"

National Inventory	Status
Australia - AICS	Y
Canada - DSL	Y

China - IECSC	Y
Europe - EINEC / ELINCS / NLP	Y
Japan - ENCS	N (petroleum distillates HFP)
Korea - KECI	Y
New Zealand - NZIoC	Y
Philippines - PICCS	Y
USA - TSCA	Y
<b>Legend:</b>	<i>Y = All ingredients are on the inventory N = Not determined or one or more ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)</i>

## SECTION 16 OTHER INFORMATION

### Other information

#### Ingredients with multiple cas numbers

Name	CAS No
formaldehyde	112068-71-0, 50-00-0, 8005-38-7, 8006-07-3, 8013-13-6
petroleum distillates HFP	64742-48-9., 64742-88-7

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

A list of reference resources used to assist the committee may be found at:

[www.chemwatch.net](http://www.chemwatch.net)

The (M)SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.